# UNIT AUTOMATIC EXCHANGES No. 13 AND No. 13X

Schedule of Equipment and Miscellaneous Items

#[MOTE:- As this Instruction has been completely revised, individual items have not been "starred"]

- Introduction. This Instruction details the main items of equipment (excluding power plant) required in connexion with the provision of a U.A.X. No. 13 or 13X; the "Small Stores" and "Small Switchboard Stores" items are detailed separately in G 3532.
  - 2. Main items required for installation are detailed in the table below.
  - 3. Exchange plant items and maintenance records, see G 5532 and G 5533.
- Power Plant. The power plant items are scheduled in POWER, General, F 3028, F 3030, and F 3060.
  - 5. Diagrams and Drawings. Diagrams and Drawings are listed in G 1532.
- Circuit Diagram Folder. The provision of a Circuit Diagram Folder No. 3 should be arranged in accordance with General, A 8052.
- 7. E.I. File. The provision of an E.I. file should be arranged in accordance with GENERAL, General, A 0010.
- 8. Parent and non-parent terminations. The equipment required at the associated parent and non-parent exchanges, for the termination of the junctions from the U.A.X., is detailed in Trunks & Junctions, E 3120.
- Cost of Non Rate Book Items. These are shown, for works estimate purposes, in WORKS, Estimates & Allocations, B 0055.

#### MAIN ITEMS REQUIRED FOR INSTALLATION

Item	Quantity	Remarks		
'C' Unit				
Unit, Auto, No. 13C	1 for U.A.X. No.13 2 " No.13X			
Brackets, Mtg. AK	4 per 'C' unit	For mounting Labels, No. 198		
" " V	2 per additional "Jacks, Test, No.4"	-		
Casing and Cover, T No. 6	As required			
Cord, Test, No. 4/72B	1	For line-testing equipment		
End Panel, for Unit, Auto, No. 130	1 for U. A. X. No. 13X	See G 3550		
Puse-mountings, No. 4001	As required	For subscribers' line termina- tions		
" No. 4028		For junction " "		
Covers, Puse-mountings, No. 4028		- Table 1		
Jacks, Test, No.4	" "	6 supplied with the unit		
Lamps No. 2, 50-V.	21 per 'C' unit	Alarm lamps, see also 'A' unit		
Mixture No. 2	As required	For sealing base of 'C' unit		

P.O. ENG. DEPT., ENG. INSTNS.

## MAIN ITEMS REQUIRED FOR INSTALLATION (contd.)

Item	Quantity	Remarks
Pegs No.18	As required	For transfer arrangements, see also "Wedges, Locking, No. 5" in G 3532
Pegs No.47	12 per Unit, Auto, Ng. 13C	
Plugs No. 222	8 " " NQ.13C	For busying junctions
Cordage, Inst., No. 1/F, Black	3 ft, per " " " )	(See G 5001 and G 5531)
Protectors, H.C. & T. 40B	As required	6 supplied with the unit
Rings, Jumper, No. 9		-
Felephone No. 1/232F, Black	1 }	
Bell-set No. 26	1 . {	Service telephone
Cord, Inst., No. S/74H, Black, 9gin.	1	
" " No.3/82B, Brown, 72in.	If required	Required at U.A.X.No.13X only, see G 3550
Troughs, Cable, TP 524	As required	-
Tester No.43	1	Recover after opening
Detector No.4	1	of the exchange
'A' Unit		
Unit, Auto., No.13A	As required	-
Blanks, Meter, 100-type	* #	
Labels, U.A.X., Set No.2	n 11	1
" " No.8	* *	Labels for linefinders,
" " No.4		group selectors, final
" " No.5		selectors and meters
" " No.6		3
Lamp No.2, 50-V.	2	For L. Fdr. and meter-test lamps
Meters No.100A	As required	Subscribere! meters
" " 1000	n n	Group-selector overflow meters
Relays No. 819MA	* *	Mounting plate (including cover), equipped with 10 subscribers' calling equipments
Selectors No. 2/3161	и г	Linefinder, max. of 8 per unit
" No. 2/3182	ч и	Final selector, " " 5 " "
" No. 2/3163		Group selector," "B " "
'B' Unit		
JAIO-ROLLS	no Luci compositivamento	
Unit, Auto., No.13B	As required	
Brackets, Mounting, BK, 278-in.	* *	For vertical-type mountings, See Dgm. TP 5121/1. Two also required for each cross-connexio frame. TP 573 refers

# MAIN ITEMS REQUIRED FOR INSTALLATION (contd.)

	I	tem				Quantity	Remarks
	'B' Un	it (	con	td.1			
Capacit	ors, H.	c.,	No.	101	5 when	n required	)For use with Strip-mounted
Clips N	0. 18,	15 1	n.		5 "		Sets AT 3945, Uniselector
Resisto	rs, Spoo	1,No	.6	- 200 ohms	5 "		Set B
Fuse-mo	untings	No.	731	A		1	Additional when required. Each unit supplied with two
Jacks: N	0. 51				As re	quired	Additional routine-test jack AT 4082 refers
Regener	eators N	lo. 1				1	For use with Strip-mounted Sets AT 4453, AT 4454, AT 4455 or AT 4456
Relay-s	et No. 2	/341	.8		As: re	quired	Auxiliary common route-discrimin- ating equipment AT 3944
Rings,	Jumper,	No.	10			.*.	\m
Strips,	Connex	cion,	No	.97			For cross-connexion frame
Shelves	, 2000/	TP 2	201	- Type U.A.	*	**	Accommodates five Relay-sets
13 Asse	mbly 1						No. 2/3418. Mounts in bottom
							position on 'B' units
Strip-R	nounted	Set	AT	3943	"-	•	B/W. junction to manual or parent exchange [superseded by Strip- mounted Set AT 4908(I/C.) and Strip-mounted Set AT 4907(O/G.)]
Strip-m	sounted	Set	AT	3945	100	**	I/C. junction from dependent U.A.X.
	nounted for Set		AT	3945, Uni-	"		For use with Strip-mounted
	ounted for Set		AT	3945, Uni÷		*	Set AT 3945. See G 3530
Strip-m	nounted	Set	AT	3947	- 11	-	O/G. junction to dependent U. A. X.
Strip-m	sounted	Set	AT	3948	"	*	O/G. junction to dependent U.A.X. (terminal traffic only)
-	**	**	ΑT	3949		**	O/G. junction to non-dependent automatic exchange
"		н	AT	3950	148	(#)	Auxiliary route-discriminating equipment (superseded by Strip- mounted Set AT 4934)
#	**		ΑT	3951		*	Auxiliary route-restricting equipment
"	**	*	AT	3955		"	I/C. junction from parent or non-dependent exchange (superseder by Strip-mounted Set AT 4906)
*	"	*	ΑT	4626	*		Part-time private wire, junction- switching equipment

P.O. ENG. DEPT., ENG. INSTNS.

MAIN ITEMS REQUIRED FOR INSTALLATION (contd.)

	Ite	m				Quantity	Remarks
1	3' Unit	100	ntd.	)			
Strip-	mounted	Set	AT	4906	As: r	equired	I/C. junction from parent or non- dependent exchange (2 circuits per base)
ir	н.		AT	4907		*	O/G. junction to parent exchange and non-parent manual exchange
"	(40)	. 11	AT	4934	"	**	Auxiliary route-discriminating equipment
	"	*	AT	4453†	"	*	O/G. junction (with pulse regener- ator) to dependent U.A.K.
	н.	*	AT	4454†	*	240	O/G. junction (with pulse regenerator) to dependent U.A.X. (terminal traffic only)
н	**	*	AT	4455†			O/G. junction with B/W. switching (with pulse regenerator) to parent exchange
**	"	**	ΑT	4456†			O/G. junction (with pulse regener- ator) to non-dependent auto exchang
	† This	a egt	tipm		e prov		n the authority of the Eng.
Unisel	Lectors	No.	2/3	3A		1	For use with Strip-mounted Sets AT 3948 and AT 3951
	-	*	2/6	AS		1	For use with Strip-mounted Sets AT 3950 and AT 4934
		**	2/4	1A	As 1	required	)For use with Strip-mounted
Brack	et, Mou	ntin				1	Sets AT 3945, Uniselector Sets:
	, Notic					1	}A & B
- 4 (84)		Uni		730			Market Control
	115.20	252-52			4.5	required	
	Auto.,				A.S.	required	For mounting Labels, No. 198
	ets, No	unti	ng,				" connexion strips
. "			- 8	CA			Connexton Surps
	mountin						
	-50			ig, No. 40	90		n
	ings, D				"		For mounting Transformers, No. 48
Parts	No. 1/	TP 1	001			1.0	-
Prote	ctors,	H.C.	& 5	1 40B	,	-	_
Rings	, - Jumpe				- T		-
	-	N	0.2	2	"	**	-
**		N	0.8	3		19	-
Strip	s, Con	nexio	n,	No	**		-
		**	3	No			-

## MAIN ITEMS REQUIRED FOR INSTALLATION (contd.)

Iten	Quantity	Remarks
'D' Unit (contd.)		
Fransformers No. 48	As required	The same of a field meaning
Units, Terminating, No.6B		_
Cables and Wires		
Cable, Switchboard, P. V. C., S. C. and L., P. V. C.		
6-wire/9‡	As required	
12-wire/9±		
20-wire/9#	" "	
31-wire/94		
41-wire/9#	* **	
50-wire/9±(10 singles + 20 pairs)	" "	
61-wire/9#	" "	
80-wire/9#		
100-wire/9‡		
12-wire/20	" "	For tones, ringing etc.
Cable, E.L., 250V., 2.0225 sq.in., Black		For negative battery and earth
" " 2507.,0.0225 sq.ih., Red		leads
" " 250V.,0.0020 sq.in., Black		For positive battery and earth
" " 250V.,0.0020 sq.in., Red		leads
Cable, P. V. C., No. 1, 2-wire/9±	* "	For charge-fail lead
Wire, P. V. C., No. 1, 1-wire/20	. "	[For alarms, tones, etc. on
" " 1-pr./20		B' units and miscellaneous uses
Wire, P.V.C., No.2		
1-wire/94		1
1-pr./94	* "	
3-wire/9#		M.D.F. & I.D.F. jumpers
4-wire/9‡		1 }
Wire, Switchboard, P.V.C.		}For commoning on connexion
S.C. and L, 1-wire/6g	1000	strips etc.
Wire, Copper, Tinned, 25 S.W.G.		
Wire, Copper, Soft, Stranded, 7/20	" "	Power switchboard earth
" " " Stranded, 19/16	* * *	Main earth

P.O. ENG. DEPT., ENG. INSTNS.

TELES., AUTO., G 3531

### MAIN ITEMS REQUIRED FOR INSTALLATION (contd.)

Item	Quantity	Remarks	
Miscellaneous		Entraction Interview	
Frames, Notice, No.8	As required		
Labels, U. A. X., Set No. 1	. "	Labels for tool cabinet	

References:-(E1/4)

References:- G 1532, G 3530, G 3532, G 5532, G 5901, G 6051

Trunks & Junctions, E 3120

GENERAL, General, A 0010 POWER, General, F 3028, F 3030, F 3060 WORKS, Estimates & Allocations, B 0055

END